

CO2 Fire Extinguishers

For use on:



- Petrol, Diesel, Oils



- Computers, Switchgear, Fax

Important for its non-damaging highly effective performance and cleanliness. Suitable for situations involving flammable liquids and electrical hazards. CO2 gas is harmless to delicate equipment and materials. Ideal for modern office environments, all electronic risks, and where oils, spirits, solvents and waxes are in use.

Unit Features:

- Durable Steel Operating Handles
- Controllable Squeeze Grip Operation
- High Grade Brass Valve Assembly to ensure Reliability and Optimise Efficiency
- Harmless to Machinery
- Corrosion Resistant Epoxy Coated Cylinder
- Factory Filled
- Complete with corresponding bracket
- CE Approved

Capacity (Kg)	2	2
Cylinder Diameter (mm)	111	105
Cylinder Height (mm)	475	475
Cylinder Volume (Ltr)	3	3
Full Extinguisher Weight (Kg)	5.2	6.2
Discharge Time Approx (secs)	8	8
Fire Rating	34B	34B
Working Pressure @ 20°C (bar)	56	56
Test Pressure (bar)	250	250
Operational Temperature Range (°C)	-20 to + 60	-20 to + 60

Capacity (Kg)	5	5
Cylinder Diameter (mm)	159	138
Cylinder Height (mm)	586	655
Cylinder Volume (Ltr)	7.5	7.5
Full Extinguisher Weight (Kg)	11.5	12.5
Discharge Time Approx (secs)	14	14
Fire Rating	89B	89B
Working Pressure @ 20°C (bar)	56	56
Test Pressure (bar)	250	250
Operational Temperature Range (°C)	-20 to + 60	-20 to + 60



Subject to change

April 2013